

working for clean rivers



Green Street Challenges and Design Considerations

Watershed Revegetation Program
Bureau of Environmental Services

Jeremy Person, PLA, LEED AP

March 2017



ENVIRONMENTAL SERVICES
CITY OF PORTLAND

NICK FISH, COMMISSIONER
MICHAEL JORDAN, DIRECTOR

Presentation Outline

Background
Challenges and Considerations
Summary
Questions






Background



Watershed Revegetation Program



- Design and Plan Review
- Facility Inspection
- Planting
- Contractor Management
- Maintenance
- Irrigation
- Tree Pruning



Adopted Bureau Level of Service (LOS)

CATEGORY (Good Effort)

- Vegetation**
- ✓ Plants are mostly healthy
 - ✓ Small quantities of weeds
 - ✓ At least 75% plant survival

- Litter**
- ✓ Small quantities of litter present

- Soils**
- ✓ Occasional bare spots
 - ✓ Erosion?

- Function**
- ✓ Checkdam condition?
 - ✓ Inlets are open no less than 50% of time

- Maintenance Effort**
- ✓ WRP staff inspect a minimum of 2 times/year
 - ✓ Maintenance crews visit sites 3-4 times/year
 - ✓ Dead plants are selectively replaced
 - ✓ Checkdams are selectively repaired/rebuilt



Level of Service

- Maintenance Activities
 - Routine (~3-4/year)
 - Inlet cleaning and sediment removal
 - Leaf and trash removal
 - Weeding
 - Periodic (as needed)
 - Tree and shrub pruning
 - Irrigation



Level of Service

- Repair Activities
 - Replanting
 - Plant coverage or health below service level
 - Structural Damage
 - Chipped/cracked curbs
 - Broken check dams, etc.



Pass



INLETS



**VEGETATION
COVER &
HEALTH**



SEDIMENT

Fail



Challenges and Design Considerations

Why is this important?

1. Provide lessons learned from field observations and maintenance history
 - Facility Design
 - Facility Siting
2. Improve feedback loop between design and maintenance

Challenges and Design Considerations

Topics Covered



- Planters and Swales
- Inlets
- Splash Pads
- Forebays
- Step-Out Zones
- Check Dams
- Soils
- Rock Galleries

Planters and Swales




Planters and Swales - Challenges

- Design type affects plant choices, plant health and maintenance costs.



Planters and Swales – Challenges

- Swales may cost less to build, but more costly to maintain.
- Zone A
 - Treatment area
- Zone B
 - Irrigation
 - Weed Intrusion
 - Pedestrian Damage




Planters and Swales – Considerations

- Advantages of planters
 - Zone A only
 - Plant installation simpler
 - Less weed intrusion
 - Flood irrigation
 - Fewer external impacts



Inlets



Inlets – Challenges

- Must allow water to enter facility
- Will clog – must be easy to clean
- Allow sediment and leaf debris to enter and be detained
- Trenches further complicate cleaning



Inlets – Considerations

- Wide openings without obstructions work best



Inlets – Considerations

- Trenches longer than an arms-reach require specialized tools
- Narrow facilities & long trenches necessitate working in the street




Inlets – Considerations

- Grates should be removable
 - Tamper-resistant vs. hex-head bolts
 - Traffic Rated




Inlets – Considerations

- Inlet opening size is very important



Splash Pads



Splash Pads – Challenges

- Must be cleaned quickly
- Need to be set level with soil (+/- 1")
- Right size for the facility



Splash Pads – Considerations

- Rock is time consuming to clean
 - Concrete works best



- Set the pad flush with the soil to reduce erosion




Splash Pads – Considerations

- Eliminate ‘dead’ space
 - Hard for plants to grow in <18” between pad and wall



Forebays




Forebays – Challenges

- Situational
- Need to drain – no standing water
- Accessible and easy to clean (concrete bottoms)



Forebays – Considerations

- Use on high-traffic streets or where there are sediment concerns




Forebays – Considerations

- Weep holes clog
- Vertical slots preferred
 - 1" - 3" wide
 - Multiple slots



Step-out Zone



Step-out Zones – Challenges

- If you build it, people will walk there
- Protect people
- Protect the City's infrastructure investment
- Needs to be durable and reduce maintenance




Step-out Zones – Lessons Learned

- Rock step-out zones subside, more maintenance
- 12' Concrete step-out more durable and low maintenance



Check Dams



Check Dams – Challenges

- Multiple options. One size does not fit all. Make the solution fit the problem
- Need to consider life-cycle costs
- Materials used: clay, rock, wood, concrete, plastic, metal




Check Dams – Considerations

- Clay core not durable
 - Clay washes out
 - Dam gets trampled or settles
- Rock dams do not detain water effectively
 - Rocks don't stay in place



Check Dams – Considerations

- Concrete dams are durable and low-maintenance
 - Makes the most sense where there is a sidewalk wall to connect to
 - Static material; cannot be easily changed



Check Dams – Considerations

- Notches are useful but can cause erosion
- Most important to get the height of the dam correct
 - Elevation must be tied to other facility elements



Check Dams – Considerations

- Wood dams best for retrofits, swales, challenging situations
 - Have used Douglas Fir, Cedar, Juniper
 - Juniper is expected to last the longest
 - Limited sizes
 - Chemically treated wood not permitted




Check Dams – Considerations

- Wood is a dynamic material and can easily be altered
- Gaps at the ends are problematic
 - Wood must be cut to fit
 - Sealant may be used




Soils




Soils – Challenges

- Filters storm water and sustains plant life
- Must infiltrate rapidly enough to get water off the street
- Current BES req.
 - 40% compost
 - 50%-60% sand
 - <10% fines (200 sieve)



Soils - Considerations

- High-sand soil mixes greatly restrict plant longevity
- Uniform soil mixes retain less water in the summer




Soils - Considerations

- Weed seeds can be imported with the soil
- Compost breaks down over time and can export phosphorus



Rock Galleries




Rock Galleries - Challenges

- Drought-related stress observed in plants in facilities with rock galleries
- Rock Galleries are useful tools, but should not be an assumed part of the facility





Rock Galleries – Considerations

- Hydraulic Conductivity (K)
 - Ratio at which fluids, such as rain water, move through soil, rock, plant roots, etc.
 - Higher K means less water suspended in soil and accessible to plant roots



Rock Galleries – Considerations

- Rock Galleries may be contributing to declining plant health
 - water drains quickly through the soil (high K) and collects at the bottom of the facility
 - Rock galleries may prevent roots from accessing this water



Summary



Recommendations – Planters and Swales

- Planters are preferred for ease of maintenance, less foot traffic, less structural issues
- Upland planting areas (Zone B) should be minimized
 - Step-out zones should be added next to on-street parking



Recommendations – Inlets

- Wide openings with no obstructions
- Trenches
 - Must accommodate tools: 12” wide and 4-5’ long
 - Removable grates with tamper resistant bolts



Recommendations – Splash Pads

- Concrete, not rock
- Set flush with soil
- If the “plantable” space behind the pad is less than 18” – extend the pad to the wall



Recommendations – Forebays

- Best used on busy, heavily traffic streets
- Larger is better
- Use slots for drainage
 - Slots should be 1”-3” wide



Recommendations – Step-Out Zones

- Identify the need early in the design process
- Use concrete step out zones
- Gravel step-out zones can be retrofitted to concrete




Recommendations – Check Dams

- “Right dam in the right place”
- Concrete is the most durable and low maintenance
- Wood is best for swales and retrofit situations
 - Look for long-lasting woods like Juniper
 - Minimize gaps at the ends of wood dams
- Make sure dam height is correct
- Notches do not need to be in the middle



Recommendations – Soils

- Need to look beyond infiltration rate alone for facility soil needs
- A good soil mix can benefit plant health and lower maintenance costs




Recommendations – Rock Galleries

- Is the rock gallery needed?
- If a tree is required, can the rock gallery be removed, reoriented, or truncated to avoid interaction with tree roots?
- Can the rock gallery be designed such that plant roots can access the native subgrade?



Green Street Program Successes

- Green Street program began with three facilities in 2003
- Grey and Green infrastructure work well together
- Overall, public acceptance of facilities has been positive




Questions

Jeremy Person
503-823-2024

jeremy.person@portlandoregon.gov



Plants in SMFs



Plants in SMFs – Challenges

- Plants must tolerate a range of conditions
- Slope, aspect, microclimate, upstream issues, heat island and sight lines (30" from top of curb)
- Safety and visibility



Plants in SMFs – Considerations

- Plant selection helps control maintenance costs
- Specify plants that perform well for site conditions
- SWMM Plant List updated based on successes



Plants in SMFs – Considerations

- Irrigation (post-establishment) is an ongoing cost
 - FY12 - \$32,000
 - FY13 - \$53,000
 - FY14 - \$50,000
 - FY15 - \$70,000
 - FY16 - \$73,000
- Lined facilities
 - 21% of our green street irrigation expense for 2015 (~\$16K) went toward watering lined facilities (9% of inventory)



Plants in SMFs – Considerations

- Visibility and pedestrian/motorist safety must be considered



Trees in SMFs



Trees in SMFs – Challenges

- Trees, while beneficial, add additional costs to long-term facility management
- Choose the right tree for the right place
 - Could be outside facility



Trees in SMFs – Considerations

- Building new facilities around existing trees creates challenges
 - Construction
 - Added stress to tree
 - BES responsibility for these trees
 - Existing tree roots can disrupt water flow




Trees in SMFs – Considerations

- Additional costs
 - Pruning
 - Seasonal leaf removal
 - Extra irrigation
 - Disease, damage, replacements




Trees in SMFs – Considerations

- Right tree, right place
 - Consider existing canopy and trees
 - Pedestrian walkways
 - Growing space



Trees in SMFs – Considerations

- Right tree, right place
 - Visibility / Signage locations



Recommendations – Plants in SMFs

- Plant selection helps control maintenance costs
- Irrigation may be required in LTM
- Site considerations are important to plant selection – “Right plant, right place”



Recommendations – Trees in SMFs

- Trees important to stormwater management
- “Right tree, right place”
- Criteria for planting a tree in a facility
 - Can the tree be placed outside the facility?

